



# VipRoc Prefinished Panels

## PRODUCT DESCRIPTION

VipRoc is a proprietary product developed by Vipco Industries for use in manufactured housing and residential applications.

VipRoc is a 1/2" drywall product with a unique composition which meets and exceeds all 1/2" standard drywall characteristics. VipRoc has been evaluated by the NRC ( CCMC # 14184-R ).

Vipco manufactures a complete line of prefinished decorative gypsum panels used in a variety of industries including manufactured housing, commercial construction as well as the modular building industry. Vipco also offers specialty products including M2Tech Mold & Moisture Resistant, Glasroc and Standard boards.

VipRoc prefinished panels are made from CertainTeed Gypsum board. Vipco offers a wide variety of in stock colours, textures and finishes.

## PRODUCT IDENTIFICATION

VipRoc Prefinished Panels have been clearly labeled on the back of the panel with its product name and CCMC Evaluation number clearly printed.

"VIPROC CCMC # 14184 - R"



VIPCO.CA

Calgary, AB 403-279-7501

## PHYSICAL PROPERTIES

**THICKNESS:** VipRoc is 1/2" thick.

**WIDTH:** Panel width is 4'

**LENGTHS:** Available lengths are 8', 9' & 10'

**EDGES:** Decorative vinyl is wrapped around to the panel backside sealing the long edges. All sides are square edge to allow battens or batten tape to cover all seams easily.

## SURFACE BURNING CHARACTERISTICS

Surface Burning Characteristics as tested in accordance with the standard CAN/ ULC S102-07. VipRoc Prefinished Panels -

Flame Spread	5
Smoke Developed	15

## STORAGE & HANDLING

Vipco prefinished panels are a finished product and should be handled with care during installation, handling and storage.

The prefinished panels should be stored inside a warehouse or other suitable structure to keep the product dry, avoiding exposure to damp wet weather.

A firm dry floor is recommended to ensure proper storing of prefinished panels. Ensure the panels are evenly supported to prevent sagging or damage to ends or edges.

## LIMITATIONS

Vipco pre-finished drywall should not be used in areas where there is continuous exposure to temperatures exceeding 125 F (52 C).

Panels are not suitable for continuous high humidity and excessive moisture areas.

## CLEANING

Gently wipe using a clean sponge, warm water and mild soap. Wipe off excess water with a clean, soft cloth. Do not use abrasive cleaners or cleaners containing chlorine bleach or solvents.